

## Questionnaire for manhole cover SD4/RC3/RC4

Project: \_\_\_\_\_

Customer: \_\_\_\_\_ Person in charge: \_\_\_\_\_ Phone: \_\_\_\_\_

Site: \_\_\_\_\_ Customer No.: \_\_\_\_\_ Fax: \_\_\_\_\_

☐ Offer Offer No.: \_\_\_\_\_ Price per unit: \_\_\_\_\_ €,

☐ Order Order No.: \_\_\_\_\_ Manufacturing costs per unit: \_\_\_\_\_ €, Item.: \_\_\_\_\_, Q: **P** \_\_\_\_\_

**Short text: Manhole cover typ SD4-RC3/RC4, design based on DIN 1239:2018-4, burglar resistant to DIN 1627 resistance class RC3 or RC4, rainproof, seal low-wear in cover, completely made of stainless steel, cover plate 4 mm thick, including lock system with anti-drilling protection, as standard with hardened safety lock as; the profile cylinder in accordance with DIN 18252 to be provided by the customer.**

### 1. Material:

☐ 1.4307 (AISI 304 L)

☐ 1.4404 (AISI 316 L)

### 2. Test certificate:

☐ RC3

☐ RC4

### 3. Test certificate:

☐ Design according to test certificate

☐ Design on the basis of the test certificate

**RC3 and RC4 Maximum clear shaft opening, one-part design, with test certificate: Ø 1200 mm**

### 4. Clear shaft opening:

Diameter Ø = \_\_\_\_\_ mm

Please note:      Ø one part:      min. 600 mm, max. 1300 mm  
                         Ø two part:      min. 1200 mm, max. 1500 mm

### 5. Design:

☐ one-part

☐ two part

☐ Cross bar rigidly welded, not removeable

☐ Cross bar screwed, removeable (clear opening is reduced by 180 mm)

☐ Cross bar hinged

### 6. Frame:

☐ Frame for bolting with dowelling clips (standard)

☐ Frame for embedding into concrete (concealed frame)

**7. Insulation and vapour hood:**

- a) ☐ insulation of the cover ☐ special insulation height of the cover : \_\_\_\_\_ mm (max. 50 mm)  
☐ insulation of the frame

- b) ☐ vapour hood DN 150, centrally welded

***For multi-part covers:***

- ☐ vapour hood on all cover parts ☐ vapour hood only left side ☐ vapour hood only right side

**8. Optional equipment:**

- ☐ Opening possibility from below (⇒ designed on the basis of the test certificate!)
- ☐ Magnetic contact (cover open/closed indicator)
- ☐ Detachable hinges, i. e. removable cover (⇒ designed on the basis of the test certificate!)
- ☐ Cover which can only be opened from below (with locking lever, without upper locking part) (⇒ designed on the basis of the test certificate!)
- ☐ Paint RAL colour: \_\_\_\_\_
- ☐ Biofilter in vapour hood (only DN 150) (odour elimination) *or*  
*(Info: retrofitting biofilter only possible with insulated covers)*
- ☐ Energy self-sufficient wind-powered ventilator
- ☐ Cover on the top of the wall executed according to customer's structural drawing (Not with frame for setting in concrete)  
Width of the on-site wall crown: \_\_\_\_ mm / Frame bending downwards: \_\_\_\_ mm

**9. Other accessories/Comments:**

.....

.....

.....

.....

**10. Sales person in charge:**

..... Phone No.: +498462/201-\_\_\_\_ Fax No.: +498462/201-399 E-mail:\_\_\_\_@huber.de

**11. Enclosures for the design engineers:**

- ☐ Drawing ☐ .....
- ☐ Photo ☐ .....

**Mounting material has to be recorded as a separate item:**

**Mounting material for SD4/RC3/RC4**

- |   |  |                |
|---|--|----------------|
| <input type="checkbox"/> X <input type="checkbox"/> | 10192423 – Mounting material for SD4/RC3/RC4 up to Ø 1000            | Price: ..... € |
| <input type="checkbox"/> X <input type="checkbox"/> | 10192582 – Mounting material for SD4/RC3/RC4 ILLMOD bis Ø 1000       | Price: ..... € |
| <input type="checkbox"/> X <input type="checkbox"/> | SPECIAL Mounting material for SD4/RC3/RC4 (Service article)          | Price: ..... € |
| <input type="checkbox"/> X <input type="checkbox"/> | 10238266 pollen filter, 1.4404, (exchangeable) in vapour hood DN 150 | Price: ..... € |