

Data Request Sheet for Doors TT7.30

Project: _____

Company: _____ Customer No.: _____ Person in charge: _____

Phone No.: _____ Fax No.: _____ E-mail: _____

☐ We hereby order:

Site: _____ Unit price _____ €, Item: _____, Q.: **P** _____

☐ We hereby ask you to submit an offer:

Site: _____ Unit price _____ €, Item: _____, Q.: **P** _____

This DATA REQUEST FORM for PRESSURE DOORS consists of two sheets. Please fill in your **complete** data, sign the form under point 9 and return the sheets to our fax number which you will find below under point 10. Please note that your data will be a binding integral part of the contract for manufacture of a pressure door. The specified delivery period begins on receipt of the **completely** filled in data request form. The optional equipment listed under point 7, which is not contained in our offer price, will only be manufactured and supplied at extra cost.

Please note: the site must be inspected prior to installation by our service!

1. Installation conditions and measures

1.1 ☐ For **embedding in concrete**, suitable to be lined on both sides (wall thickness 300 - 500 mm)

Please tick.	Clear door opening width (B)	Clear door height (H)
	80 cm	80 cm
	80 cm	120 cm
	80 cm	160 cm
	80 cm	180 cm
	100 cm	200 cm

(Other sizes are not available.)

1.2 ☐ For retrofitting, **bolted fixing** in a wall opening, including fixing material and seal between the frame and wall. Space requirements for the frame: 180 mm, circumferential frame on four sides

Please tick.	Clear door opening width (B)	Required wall opening width	Clear door height (H)	Required wall opening height
	80 cm	83 cm	80 cm	83 cm
	80 cm	83 cm	120 cm	123 cm
	80 cm	83 cm	160 cm	163 cm
	80 cm	83 cm	180 cm	183 cm
	100 cm	103 cm	200 cm	203 cm

(Other sizes are not available.)

Installation requirements for retrofitting:
Level ground, deviation tolerance: ± 1 mm per m,
Concrete strength class: C25/30 according to DIN EN 206-1

2. Wall thickness:

Wall thickness: _____ cm

Please note: minimum wall thickness ≥ 30 cm for all designs.

3. Frame prepared for:

☐ Straight wall

4. Material

☐ Stainless steel 1.4404 (AISI 316 L)

☐ Stainless steel 1.4307 (AISI 304 L)



5. Lock:

☐ Central lock, easy to operate from both sides

6. Door opening options:

☐ Hinges on left

☐ Hinges on right



7. Optional equipment

☐ Sanding of parts from the frame in contact with concrete

☐ Potential equalisation (hinge side)

☐ Door arrestor with take up wedge (50166177)

☐ Vent holes in the frame

8. Delivery address

Please quote the full delivery address including post code and place name. Additionally indicate the availability times during which delivery of goods is possible and the name of contact persons if the equipment is to be delivered directly to the site.

.....
.....

9. Customer's confirmation:

Customer's representative: _____

Date: _____

Signature: _____

10. Please return this form to:

HUBER contact person:

Review: Reviewed at HUBER SE by: _____

11. Enclosures for the design engineers:

☐ Drawing

☐ Photo

☐

☐